

Automatic Railroad Jumper Cable Tester



INTRODUCTION

The Automatic Railroad Jumper Cable Tester is a microprocessor-controlled tester designed to automatically perform Hi-Pot and Ten Ampere Continuity (Current) tests on Railroad Jumper Cables. The tester pictured above is configured for the Long Island Railroad's C-3 fleet of commuter trains and may be easily configured to test other jumper cables.

Due to exposure to vibration, weather and EMI, jumper cable failure is frequently the cause of a multitude of intermittent elusive system problems. Many of these problems can be avoided if jumper cables are periodically tested.

Operating the tester involves turning power on and following screen prompts that were designed for ease of operation. Plug in the cable, Push a start switch, Flex the cable (for intermittent checks), Read the pass or fail completion message. A cable will be deemed "Good" only after it has successfully completed both the Hi-Pot and Current Continuity test. Should the tester detect a failure, the blinking red failure message will identify the wire path(s) responsible for the failure.

In the Hi-Pot mode, the tester will apply up to 1700 peak voltage between each pin to all other pins (630 tests for a 36 pin cable) within a two minute time frame. A Hi-Pot failure will be detected if/when dielectric leakage current exceeds 0.5 milliamperes. For Current Testing, a failure will be detected if/when less than ten Amperes of current flows through any wire path.

APPLICATION

- Used for periodic preventative maintenance testing.
- Used for incoming inspection of new cables.
- Used for troubleshooting questionable system problems that may be caused by intermittent cables.

INCLUDED ACCESSORIES

Electric High Voltage Lineman Safety Gloves

FEATURES

- Ease of Use, Microprocessor Controlled, Single Switch Operation, No Training Required
- Large 10 in. Diagonal Color Display
- Color Coded Status Messages - Instructions in Blue, Status Green, Failure Blinking Red
- Rugged, 11 Gauge Steel Front Panel and Enclosure
- Ground Fault Circuit Interrupter
- Emergency Red Pushbutton, Power-off Circuit

INSTRUMENT SIZE

Depth: 813 mm (32 in.)
Height: 914 mm (36 in.)
Width: 1,524 mm (60 in.)

WEIGHT

272 kg (600 lb.)

CONNECTIONS

Electrical: 110/220 50/60 Hz

ORDERING INFORMATION

Catalog number 06-12

**The TMI Group
of Companies**



www.testingmachines.com

Testing Machines Inc. 40 McCullough Drive, New Castle, DE 19720 USA
Tel: 800-678-3221 (USA) or (302) 613-5600, Fax: (302) 613-5619, e-mail: info@testingmachines.com

Büchel BV t/a Messmer Büchel Fokkerstraat 24, 3905 KV Veenendaal, Netherlands
Tel: +31 (0)318 521500, Fax: +31 (0)318 540358, e-mail: buchel@testingmachines.com

Lako Tool 7400 Ponderosa Road, Perrysburg, OH 43552 USA
Tel: (419) 662-5256, Fax: (419) 662-8225

Lawson Hemphill 1658 G A R Highway, Swansea, MA 02777 USA
Tel: (508) 679-5364, Fax: (508) 679-5396, e-mail: information@lawsonhemphill.com

Adamel Lhomargy SAS Z.A. de l'Habitat, Batiment 6, Route d'Ozoir, 77680, Roissy en Brie, France
Tel: +33 (0)1 64409210, Fax: +33 (0)1 64409211, e-mail: adamellhomargy@testingmachines.com

TMI Canada 40 McCullough Drive, New Castle, DE 19720 USA
Tel: (302) 613-5600, Fax: (302) 613-5619 e-mail: canada@testingmachines.com