

Folding Force Tester



INTRODUCTION

Box plants utilize the Folding Force Tester to monitor scoring equipment to ensure box performance. Corrugated converters use the Folding Force Tester to monitor converting operations and make adjustments to improve quality and end users utilize the Folding Force Tester to ensure the boxes they purchase will run effectively on their production line.

APPLICATIONS

Corrugated

SPECIFICATIONS

- Maximum measured force: 30 N (7 lb)
- Accuracy: 0.5%

FEATURES

- Easy to use
- Printer supplied for hard copy printout
- Quick and simple
- Results are automatically stored
- Running average and standard deviation are calculated and displayed

- High throughput
- Peak force, Score ratio, and Peak force at angle modes

INSTRUMENT SIZE

Depth: 230 mm (9.1 in.)
Height: 95 mm (3.7 in.)
Width: 350 mm (13.8 in.)

WEIGHT

10 kg (22 lb)

CONNECTIONS

Electrical: Specify voltage requirements when ordering

ORDERING INFORMATION

Catalog number 31-02

The TMI Group of Companies



www.testingmachines.com

Testing Machines Inc. 2 Fleetwood Court, Ronkonkoma, NY 11779 USA
Tel: 800-678-3221 (USA) or (631) 439-5400, Fax: (631) 439-5420, e-mail: info@testingmachines.com

Messmer Instruments Ltd. Unit F1 Imperial Business Estate, West Mill, Gravesend, Kent DA11 0DL UK
Tel: +44 (0)1474 566488, Fax: +44 (0)1474 560310, e-mail: messmer@testingmachines.com

Büchel BV Fokkerstraat 24, 3905 KV Veenendaal, Netherlands
Tel: +31 (0)318 521500, Fax: +31 (0)318 540358, e-mail: buchel@testingmachines.com

Adamel Lhomargy SAS Z.A. de l'Habitat, Batiment 6, Route d'Ozoir, 77680, Roissy en Brie, France
Tel: +33 (0)1 64409210, Fax: +33 (0)1 64409211, e-mail: adamellhomargy@testingmachines.com

TMI Canada 6 Ronald Drive, Montreal West, Quebec H4X 1M8
Tel: (514) 489-8491, Fax (514) 489-6044, e-mail: canada@testingmachines.com